Model:
OneTouch® Ping™ glucose management system

Dim [mm]
50.8 x 82.55 x 21.59

Volume
5.525 ci 90.54cc

Weight [oz]
3.9 oz

Reservoir Size
200 plastic

Connection
Luer Lock

Screen Size
992 sq mm color screen

Colors
Blue, Silver, Black, Pink, Green

Basal Increment
0.025u

Total Basals
12/day

Basal Profiles
4

Basal Interval
30 min

Basal Delivery
Varies, at 0.2 u/hr and above every 3 minutes

Temp Basal
-90% to +200% in increments of 10% for 0.5 to 24 hours (30 min increments)

Bolus Increments
0.05 Visual or 0.1, 1.0 or 5.0 audio

Carbohydrate and Correction Factors
Yes, carbohydrate and blood glucose values can be entered into the pump or meter-remote.

Bolus Type
Units or Carbs: standard, extended or combination

1 u Bolus Duration
1 or 3 sec

Battery
Pump uses 1 AA lithium or AA alkaline

Battery Life
4-6 weeks with lithium
2-4 weeks with alkaline

Motor
DC

Memory
Non-volatile:
- 500 boluses
- 270 basals
- 120 daily totals
- 60 alarms
- 60 primes
- 900 blood glucose levels

Software Download
ezManager® Max Downloads in 3 minutes with dongle and software that are available at Animas

Waterproof
12 ft for 24 hours

Extra Features
Only pump with both full feature pump & meter-remote. Meter-remote offers remote (wireless) bolus calculation and delivery within a rage of approximately 10 feet. ezCarb software stores up to 500 food items from CalorieKing® database on the meter-remote. Calculator features for carbohydrates, blood glucose corrections and insulin; reminders for time of day and when to perform blood glucose checks. Pump and meter-remote are available in Spanish. PC and MAC downloads are available with ezManager ® Max software.

Guarantee
4 years